

NO. OF CORES	CROSS SECTIONAL AREA mm ²	THICKNESS OF INSULATION mm	OVERALL DIAMETER mm	WEIGHT kg/km
1	1	0.8	5.7	50
1	1.5	0.8	5.8	52
1	2.5	0.9	6.5	67
1	4	1	7.4	92
1	6	1	8.1	119
1	10	1.2	9.8	185
1	16	1.2	11.35	258
1	25	1.4	13.3	375
1	35	1.4	14.6	485
1	50	1.6	17.2	669
1	70	1.6	19.35	892
1	95	1.8	22.2	1160
1	120	1.8	24.3	1436
1	150	2	25.9	1748
1	185	2.2	29.7	2142
1	240	2.4	31.5	2698
1	300	2.6	36.5	3348
1	400	2.8	40.4	4293
1	500	3	42.6	5262
1	630	3	47.2	6790
2	1	0.8	8.1	94
2	1.5	0.8	9	120
2	2.5	0.9	10.7	173
2	4	1	12.3	239
2	6	1	13.8	313
2	10	1.2	18.6	563
2	16	1.2	21.7	830
2	25	1.4	25.8	1211
3	1	0.8	8.74	117
3	1.5	0.8	8.74	147
3	2.5	0.9	9.68	123
3	4	1	11.48	297
3	6	1	13.2	390
3	10	1.2	14.78	705
3	16	1.2	19.9	1031
3	25	1.4	23.31	1512
3	35	1.4	27.7	1907
3	50	1.6	30.2	2651
3	70	1.6	35.8	3484
3	95	1.8	40.1	4594
4	1	0.8	9.63	142
4	1.5	0.8	46.4	180
4	2.5	0.9	9.63	260
4	4	1	14.6	336
4	6	1	16.4	449
4	10	1.2	21.8	833
4	16	1.2	25.4	1138
4	25	1.4	30.7	1714
4	35	1.4	33.4	2204
4	50	1.6	39.6	3029
4	70	1.6	44.9	4121
4	95	1.8	51.9	5361
4	120	1.8	55.3	6546
4	150	2	60.8	8095
4	185	2.2	65.7	9652
4	240	2.4	75.7	12614
5	1.5	0.8	11.8	206
5	2.5	0.9	14	297
5	4	1	16.2	422
5	6	1	18.2	567
5	10	1.2	24	1010
5	16	1.2	28.2	1400
5	25	1.4	33.9	2096
5	35	1.4	37.2	2700
5	50	1.6	44	3730
5	70	1.6	48	5033
5	95	1.8	53.2	6271
7	1.5	0.8	15.13	315
7	2.5	0.9	17.6	445
12	1.5	0.8	18.2	493
12	2.5	0.9	21.4	702
19	1.5	0.8	22.1	710