

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA	CONDUCTOR DIAMETER	MINIMUM OVERALL DIAMETER	MAXIMUM OVERALL DIAMETER	NOMINAL WEIGHT
	mm ²	mm	mm	mm	kg/km
1	1.5	1.5	5.7	7.1	50
1	2.5	1.9	6.3	7.9	70
1	4	2.4	7.2	9	100
1	6	3	7.9	9.8	130
1	10	3.9	9.5	11.9	200
1	16	4.9	10.8	13.4	280
1	25	6.1	12.7	15.8	400
1	35	7.3	14.3	17.9	510
1	50	8.9	16.5	20.6	710
3	1.5	1.5	9.2	11.9	150
3	2.5	1.9	10.9	14	210
3	4	2.4	12.7	16.2	280
3	6	3	14.1	18	370
3	10	3.9	19.1	24.2	660
3	16	4.9	21.8	27.6	920
3	25	6.1	26.1	33	1360
3	35	7.3	29.3	37.1	1820
3	50	8.9	34.1	42.9	2500
4	1	1.2	9.2	11.9	150
4	1.5	1.5	10.2	13.1	190
4	2.5	1.9	12.1	15.5	260
4	4	2.4	14	17.9	350
4	6	3	15.7	20	460
4	10	3.9	20.9	26.5	830
4	16	4.9	23.8	30.1	1190
4	25	6.1	28.9	36.6	1720
4	35	7.3	32.5	41.1	2260
7	1.5	1.5	15	19	340
7	2.5	1.9	17.5	21.5	500
12	1.5	1.5	17.6	22.4	530
12	2.5	1.9	20.6	26.2	720
18	1.5	1.5	20.7	26.3	700
24	1.5	1.5	24.3	30.7	960
36	1.5	1.5	27.8	35.2	1360