

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm		NOMINAL WEIGHT kg/km	BW / CW GLAND	WRAPAROUND CLEATS
			UNDER ARMOUR	OVERALL			
2	1.5	0.6	7.3	12.1	302	20	CC5
2	2.5	0.7	8.5	13.6	346	20	CC6
2	4	0.7	9.4	14.7	410	20S	CC7
2	6	0.7	10.5	15.9	499	20	CC7
2	10	0.7	12.3	18	648	20	CC8
2	16	0.7	14.3	20.4	978	20	CC9
2	25	0.9	14.7	20.4	1290	25	CC9
2	35	0.9	16.8	23.3	1500	25	CC10
2	50	1	19	25.8	1890	25	CC11
2	70	1.1	22	29	2450	32	CC12
2	95	1.1	25.1	33.1	3300	32	CC14
2	120	1.2	27.9	36.1	4020	40	CC16
2	150	1.4	30.9	39.3	4750	40	CC16
3	1.5	0.6	7.8	12.6	330	20	CC5
3	2.5	0.7	9.2	14.1	390	20S	CC6
3	4	0.7	10	15.3	464	20S	CC7
3	6	0.7	11.2	16.6	568	20	CC7
3	10	0.7	13.1	19.5	866	20	CC8
3	16	0.7	15.3	21.6	1152	25	CC9
3	25	0.9	18.9	23.6	1800	25	CC11
3	35	0.9	21.3	25.7	2230	32	CC12
3	50	1	21.7	28.5	2490	32	CC12
3	70	1.1	25.2	32.2	3290	32	CC14
3	95	1.1	28.8	37	4440	40	CC16
3	120	1.2	32	40.4	5470	40	CC16
3	150	1.4	35.9	45.5	6930	50S	CC18
3	185	1.6	40	49.8	8350	63S	CC20
3	240	1.7	44.9	55.1	10400	63S	-
3	300	1.8	49.8	60.2	12600	63S	-
3	400	2	55.8	66.6	14600	75S	-
4	1.5	0.6	8.5	13.3	365	20S	CC6
4	2.5	0.7	9.9	15	438	20	CC6
4	4	0.7	11	16.4	532	20	CC7
4	6	0.7	12.3	18.7	764	20	CC8
4	10	0.7	14.5	21.1	1013	25	CC9
4	16	0.7	17	23.4	1360	25	CC10
4	25	0.9	21	26.1	2160	32	CC11
4	35	0.9	23.6	28.6	2690	32	CC12
4	50	1	25	32	3130	32	CC14
4	70	1.1	29.5	37.7	4500	40	CC16
4	95	1.1	33.3	41.7	5600	50S	CC18
4	120	1.2	37.5	47.1	7400	50	CC20
4	150	1.4	41.6	51.4	8780	50	-
4	185	1.6	46.4	56.6	10630	63S	-
4	240	1.7	52.6	63	13390	63	-