

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CONDUCTOR TYPE	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
1	2.5	RE	0.8	1.4	6.15	62
1	4	RE	1	1.4	7.5	85
1	6	RE	1	1.4	7.5	108
1	10	RM	1	1.4	8.6	155
1	16	RM	1	1.4	9.6	218
1	25	RM	1.2	1.4	11.1	318
1	35	RM	1.2	1.4	12.1	414
1	50	RM	1.4	1.4	13.7	552
1	70	RM	1.4	1.4	15.5	750
1	95	RM	1.6	1.5	17.6	1020
1	120	RM	1.6	1.6	29.3	1259
1	150	RM	1.8	1.6	21	1546
1	185	RM	2	1.7	23.2	1913
1	240	RM	2.2	1.8	26.2	2471
1	300	RM	2.4	2	29.2	3097
2	1.5	RE	0.8	1.8	10	147
2	2.5	RE	0.8	1.8	10.7	179
2	4	RM	1	1.8	13	268
2	6	RM	1	1.8	14.2	337
2	10	RM	1	1.8	16.2	472
2	16	RM	1	1.8	18.2	644
3	1.5	RE	0.8	1.8	10.4	166
3	2.5	RE	0.8	1.8	11.3	212
3	4	RE	1	1.8	13.1	299
3	6	RM	1	1.8	15	402
3	10	RM	1	1.8	17.1	570
3	16	RM	1	1.8	19.2	789
3	25	RM	1.2	1.8	22.1	1141
3	35	RM	1.2	1.8	24.1	1462
3	50	RM	1.4	1.8	27.6	1964
3	70	RM	1.4	2.1	36.3	3635
3	95	RM	1.6	2.2	40	4488
4	1.5	RE	0.8	1.8	11.6	198
4	2.5	RE	0.8	1.8	12.1	252
4	4	RM	1	1.8	15.1	391
4	6	RM	1	1.8	16.5	465
4	10	RM	1	1.8	18.6	702
4	16	RM	1	1.8	21.1	992
4	25	RM	1.2	1.8	24.2	1431
4	35	RM	1.2	1.8	26.6	1861
4	50	RM	1.4	1.9	30.9	2535
4	70	RM	1.4	2.1	35.1	3441
4	95	RM	1.6	2.2	40.4	4691
4	120	RM	1.6	2.4	44.2	5757
4	150	RM	1.8	2.5	48.5	7095
4	185	RM	2	2.7	53.9	8810
4	240	RM	2.2	2.9	61.1	11400
5	1.5	RE	0.8	1.8	12	232
5	2.5	RE	0.8	1.8	13.1	302
5	4	RM	1	1.8	16.6	477
5	6	RM	1	1.8	18.2	618
5	10	RM	1	1.8	20.3	853
5	16	RM	1	1.8	23.1	1212
5	25	RM	0.8	1.8	26.6	280
7	1.5	RE	0.8	1.8	16.6	477
7	2.5	RE	0.8	1.8	14.1	368
12	1.5	RE	0.8	1.8	16.6	475
12	2.5	RE	0.8	1.8	18.2	628
14	1.5	RE	0.8	1.8	17.1	515
19	1.5	RE	0.8	1.8	18.9	648
19	2.5	RE	0.8	1.8	20.3	843
27	1.5	RE	0.8	1.8	22.6	895